

# RONGTA RP328

1. Compatible for 80mm and 58mm thermal paper roll
2. Wall mount function
3. Large storage (paper mode) and paper near end optional
4. High printing speed 250mm/s
5. Mainly adopt R angle and waist shape design; delicate and compact appearance



|                        |  |   |
|------------------------|--|---|
| Print                  | Printing Method  | Thermal Line                                      |
|                        | Printing Speed   | 250mm/s   |
|                        | Resolution   | 203dpi  |
|                        | Effective Printing Width   | 72mm & 48mm                                       |
| Character              | Character Set  | ANK,GB18030(Chinese)                              |
|                        | Print Font   | ANK: 12 x24,9x17, Chinese: 24 x 24                |
|                        | Character per Line   | 48-font A/64-font B                               |
| Paper Spec             | Paper Type   | Thermal paper                                     |
|                        | Paper Width  | 80mm & 58mm                                       |
|                        | Paper Roll Diameter  | Max: 80.0mm                                       |
| Paper Supply Method    |  | Drop-in paper load                                |
| Reliability            | MCBF   | 60 million lines                                  |
|                        | Auto Cutter  | 1.5 million cuts                                  |
|                        | TPH  | 100km   |
| Barcodes               | UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128 |   |
| Emulation              |  | ESC/POS   |
| Driver                 |  | WIN2003/WINXP/WIN7/WIN8/WIN10/LINUX/Mac           |
| Sensor                 |  | Paper End Sensor, Paper Near End Sensor(Optional) |
| Drawer Port            |  | RJ11  |
| Interface              |  | U、 L、 L-P、 US、 UP、 U-P、 USE、 USE-P、 BU、 WU、 WBU   |
| Network                | Wire   | TCP/IP Ethernet interface (10M/100M)              |
|                        | Wireless   | 802.11 b/g/n, BT4.0 double mould                  |
| Power Supply (Adapter) |  | AC100 ~240V(± 10%) DC 24V, 2.5A                   |
| Auto cutter            | Type   | straight knife                                    |
|                        | Life   | 1,500,000 cuts                                    |

